


DS-1LN6UZC0

U/UTP Cat6 PVC 24AWG Cable

Key Feature

- Stable electrical performance, compliant with ANSI/TIA-568.2-D, IEC61156, ISO/IEC11801.
- Compliant with RoHS 2.0.
- Sheath with strong mechanical properties, and high tensile and compressive strength, reducing damage during the project.
- Excellent performance in the Fluke 90-meter permanent link test while working continuously at 50°C high temperature.
- Excellent performance in the Fluke 100-meter channel test while being continuously loaded with 57V/1A DC power (PoE).
- Solid-Bare Copper conductor with less resistance, and better electrical properties and transmission performance.



Specification

Model	DS-1LN6UZC0	
Category	Cat.6	
Reference standard	ISO/IEC11801, ANSI/TIA-568.2-D, RoHS 2.0	
Fire resistance	No	
Conductor	Material	Solid-Bare Copper (99.95%)
	Diameter	0.50 ± 0.01 mm 24AWG
Insulation	Material	HDPE
	Diameter	0.88 ± 0.05 mm
Sheath	Thickness	0.50 ± 0.05 mm
	Diameter	5.30 ± 0.50 mm
	Material	PVC
	Color	Grey, Orange
Rip-cord	Yes	
Separator	Yes	
Sheath physical properties	Before aging	Tensile strength ≥ 13.5 Mpa Elongation ≥ 150%
	Aging period	100°C × 24h × 10d
	After aging	Tensile strength ≥ 12.5 Mpa Elongation ≥ 125%
	Cold bend	-20 ± 2°C × 4h, 8 × cable O.D, no visible cracks
Electrical Characteristics (20°C)	1.0-250.0 MHz impedance	100 ± 15 Ω
	1.0-250.0 MHz delay skew	≤ 45 ns/100 m
	DC resistance	≤ 9.38 Ω/100 m
	DC conductor resistance unbalance	≤ 4.0%
	Package dimension	390 mm X 390 mm X 210mm
	Weight	9.9 ± 0.5 kg
	Cable length	(305 ± 1.5) m
	Ambient temperature	-20°C to 70°C
Operating voltage	57 V	

Technical Performance (Fluke 90-meter permanent link)

Frequency (MHz)	Insertion Loss (dB)	NEXT (dB)	RL (dB)	ACR-N (dB)	ACR-F (dB)	PS NEXT (dB)	PS ACR-N (dB)	PS ACR-F (dB)
1	3.0	65.0	19.1	62.0	64.2	62.0	59.0	61.2
4	3.5	64.1	21.0	60.6	52.1	61.8	58.3	49.1
8	5.0	59.4	21.0	54.4	46.1	57.0	52.1	43.1
10	5.5	57.8	21.0	52.3	44.2	55.5	49.9	41.2
16	7.0	54.6	20.0	47.6	40.1	52.2	45.2	37.1
20	7.9	53.1	19.5	45.2	38.2	50.7	42.8	35.2
25	8.9	51.5	19.0	42.7	36.2	49.1	40.2	33.2
31.25	10.0	50.0	18.5	40.0	34.3	47.5	37.6	31.3
62.5	14.4	45.1	16.0	30.8	28.3	42.7	28.3	25.3
100	18.6	41.8	14.0	23.3	24.2	39.3	20.7	21.2
200	27.4	36.9	11.0	9.6	18.2	34.3	7.0	15.2
250	31.1	35.3	10.0	4.2	16.2	32.7	1.6	13.2

Available Model

DS-1LN6UZC0

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

