CP PLUS

CP-SAVW-HPU4H2-65

10/100 4 PoE Ports with 2 10/100 Mbps Uplink Ports

- 4 10/100Base PoE ports, 2 10/100Base-T uplink ports
- Standard IEEE802.3 10Base-T, IEEE802.3u 100Base-TX, IEEE802.1W Spanning Tree, IEEE 802.3x flow control
- Surge protection 6KV commo mode/ 4KV differential mode
- PoE Power 25.4W
- Easy and safe installation

System Overview

As most of the CP PLUS products have been integrated with the Power of Ethernet technology which makes trouble-shooting easier in case any errors occur. This can be done with the help of a PoE Switch makes increases reliability rapidly.

Functions

Better Connectivity

This PoE Switch has designed for outstanding power with flexible placement for better and advanced connectivity between network devices.

CE FC RoHS COMPLIANT ONVIF

CP PLUS

CP-SAVW-HPU4H2-65
10/100 4 PoE Ports with 2 10/100 Mbps Uplink Ports

Functions

Switching Performance

This PoE Switch offers the forwarding capacity to simultane-ously process traffic on all ports at line rate without any packet loss.

LED Indicator

LED lights have been installed in this Ethernet Switch to work as indicators for you to realize simple work statement reminders and clear the troubles

Easy to Use

This PoE Switch is quite easy to install and use. It requires no configuration and installation. With outstanding perfor-mance and quality, This PoE Switch is a great selection for expanding your home or workplace network.

6KV Surge Protection

6KV is an internal electrical wiring standard which means that when large currents enter the device, the clamping voltage in-creases as well, so there will be a large amount of destructive energy getting passed through the 6KV protection. The 6KV surge protection is a feature in this PoE Switch that was de-signed to protect all the connected electrical devices from volt-age spikes.

About CP PLUS

The brand that is on its way to lead the world when it comes to the security and surveillance industry, CP PLUS, keeps bombarding the market with the most reliable range of products that have been designed carefully and methodically to automate the whole surveillance and security process, no matter how big your premises are.

It was the initiative to help the public in the area where they are the most vulnerable and to empower the sense of safety in our hearts that had conceptualized CP PLUS. And embarking on its mission to make the world a safer and more secure place has taken the brand's journey to unprecedented levels even when compared to international competitors.

CP PLUS

CP-SAVW-HPU4H2-65

10/100 4 PoE Ports with 2 10/100 Mbps Uplink Ports

Feature	Specification
PoE Standard	IEEE802.3 10Base-T, IEEE802.3u 100Base-TX, IEEE802.1W Spanning Tree, IEEE 802.3x flow control
Data Transmission Port	1×4 RJ45, 1×2 RJ45
Transmission Rate	10/100Mbps auto-negotiate
Transmission Distance	10Base-T: ≤250m, 100Base-TX: ≤100m
Forwarding Mode	Store and forward
Transmission mode	Support Half/Full duplex Mode
MAC Address List	2K
Case space	768Kb
Jumbo Frame	2048b
Packet Forwarding Rate	1.488Mpps@64byte
Bandwidth	2G
Power Indicator	Green Power
Ethernet indicator	Green per ethernet port
DIP switch indicator	Green extend mode
DIP switch	100m: Standard mode - All ports can communicate with each other, 250m:Extend mode, port 1-4 are isolated from each other, transmission distance can up to 250m, and can communicate with port 5-6
Power Input	AC100~240V, 50Hz
Power Consumption	Standby: ≤3W; whole: ≤96W
PoE Pin	1/2+, 3/6-
The Port max. Rate	≤25.4W

Feature	Specification
Operating Temperature	-20°C ～60°C
Storage Temperature	-40°C ～85°C
Operating Humidity	5%～95% non-condensing
Heat dissipation method	Natural Heat dissipation
Dimensions	201mm × 140mm × 44mm
Weight	0.7kg