GRAPHICS CARDS

GeForce RTX™ 4060 Ti VENTUS 2X BLACK 8G OC



SPECIFICATIONS

Model Name	GeForce RTX™ 4060 Ti VENTUS 2X BLACK 8G OC
Graphics Processing Unit	NVIDIA® GeForce RTX™ 4060 Ti
Interface	PCI Express® Gen 4 x16 (uses x8)
Core Clocks	Extreme Performance: 2580 MHz (MSI Center) Boost: 2565 MHz
CUDA® CORES	4352 Units
Memory Speed	18 Gbps
Memory	8GB GDDR6
Memory Bus	128-bit
Output	DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR and 8K@60Hz HDR and Variable Refresh Rate (VRR) as specified in HDMI™ 2.1a)
HDCP Support	Y
Power consumption	160 W
Power connectors	8-pin x 1
Recommended PSU	550 W
Card Dimension (mm)	199 x 120 x 42 mm
Weight (Card / Package)	546 g / 783 g
DirectX Version Support	12 Ultimate
OpenGL Version Support	4.6
Maximum Displays	4
G-SYNC® technology	Y
Digital Maximum Resolution	7680 x 4320

FEATURES

Dual Fan

Two fans and a huge heatsink ensure a cool and quiet experience for you.

TORX FAN 4.0

A masterpiece of teamwork, fan blades work in pairs to create unprecedented levels of focused air pressure.

Reinforcing Backplate

The reinforcing backplate features a flow-through design that provides additional ventilation.

Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.

MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.

Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.

CONNECTIONS



1. DisplayPort
2. HDMI™

Generated 2024-03-21, check for the latest version www.msi.com/datasheet. The information provided in this document is intended for informational purposes only and is subject to change without notice.

© 2024 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.© 2024 NVIDIA, the NVIDIA logo, GeForce, SHIELD, and NVIDIA G-SYNC are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries.