

DEFENDER DUO

4G SOLAR LINKAGE CAMERA





Features:















• 3MP+3MP, Enjoy a HD image

- 2 inch body, engineering plastic material, outdoor rainproof, fashionable, beautiful and exquisite
- Solar panel powered, 4G connectivity, 100% wireless
- Dual-lens zoom design, 10x electronic magnification, close focus for panoramic view, far focus for details
- Built-in PIR motion sensor to trigger recording and alert immediately
- 350° horizontal, 150° vertical view
- Support Micro SD card storage which ensures safe storage of video data
- Support MIC and speaker, support two-way audio with clear voice
- Employ both a white light and infrared light, support both B/W night vision and full color night vision
- Achieve active defense. Support humanoid detection. The device can sound an alarm and turn on a light when someone breaks into the monitoring area. And the real-time alarm push information is available
- Support remote monitoring on mobile phones and PC to view the live video anytime, anywhere
- Ultra-low power consumption, ultralong standby
- IP66 waterproof, 4000V lightning protection, anti-surge
- Three ways to install: ceiling, wall, and pole mounting



S	pecification	S-SSD-PTZ8
Camera & Lens	Pixel	3MP + 3MP
	Sensor	1/2.8" CMOS
	Lens	4mm fixed lens
	PIR Range	8 M, 120
	LEDs	Infrared LED + White LEDs
	Supplement Light Range	20-30 M / 66-99 FT
	Min. illumination	Color: 0.1Lux, B/W:0.01 Lux
Video	Video Compression	H.265
	Resolution	Mainstream: 2304*1296, Substream: 800*448
	Max. Resolution	2304*1296
	Frame Rate	15 fps
	Day/Night	ICR (IR-cut Filter)
	DNR	3D DNR
	WDR	Digital WDR
Audio	Audio Compression	AAC, G.711
	Audio Function	Two-way audio
Alert	Alert Type	PIR+ humanoid, Motion detection
	Alert Information	Alert push notification
Storage	Storage Slot	Micro SD card (Max. 256GB)
	Cloud Storage	Support (Optional)
Ы	Horizontal View	350°
	Vertical View	90°
Operating Battery	Туре	4×21700 rechargeable lithium batteries
	Capacity	18000mAH
	Indicator Light	Red and green bi-color LED
	Button	1× reset button
	Recording Mode	Alert recording
4G	4G band	FDD-LTE: B1/B3/B5/B8; TDD-LTE:B34/B38/B39/B40/B41
General	Operating Temperature	-20°C ~ 50°C
	Input Power	Type-C 5V/1A
	Solar Panel	7W