



Introducing **ESYPOS ETP 5311N** For Smarter & Faster Billing

- Smooth & Solid Printing
- With USB + Ethernet Ports
- High Speed Printing upto 250mm/s
- Reliable Print Head Mechanism
- Supported by ESY Max Uptime Performance

Model ESYPOS ETP 531 1N POS THERMAL PRINTER		
Print	Printing method	Direct thermal line
	Printing speed	72 mm
	Dot Density	8dot/mm, 576 dot/line
	Print speed	250mm/s
	Interface	Ethernet+USB
	Paper width	79.5±0.5mm
	Paper diameter	83mm
	Line space	3.75mm (Adjustable)
Character N Barcode	Columns	Font A - 42columns or 48columns Font B - 56columns or 64columns Simplified/Traditional Chinese 21 columns or 24columns
	Character size	ANK Font Font A: 12x24dots Font B: 9x17dots Simplified/Traditional Chinese: 24x24dots
	Code page	PC437/Katakana/PC850/PC860/PC863/PC865/ WestEurope/Greek/Hebrew/EastEurope/Iran/PC1252/PC866/ PC852/PC858/IranII/Latvian/Arabic/PT151,1251/ PC737/WPC1257/ThaiVietnam/PC864/PC1001/ (Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/ (Vietnam)/(Thai)
	Barcode type	UPC-A/ UPC-E/ EAN13/ EAN8/ CODE39/ ITF25/ CODABAR/ CODE93/ CODE128/ QRCODE/ PDF417/ Data matrix
	Fonts	ASCII/GB18030(Chinese)/BIG5
Buffer	Data	48K bytes
	NV Flash	256K bytes
Power	Cashdrawer out	DC 24V/1A
	Power supply	DC 24V/1.5A
	Power adaptor	Input: AC 220V, 50-60Hz Output: DC 24V/1.5A
Physical Properties	Weight	1.10kg
	Dimension	179*152*118mm(W*L*H)
Environment	Working	Temperature: 5-50°C Humidity: 10-80%
	Storage	Temperature:-20-60°C Humidity: 10-90%
Reliability	Mechanism	150km
	Auto cutter	1.5 million cuts

ESYPOS

The Complete Retail POS Ecosystem

